

Salsa chimes



0416 50



0416 46



0416 15



0416 32



0420 25



0412 19

Pack	Cat. Nos.	Salsa 2 note electromechanical chimes
		Concerto Tone level : 80 dB at 1 m Dimensions : 177 x 104 x 45 mm
1	0416 50	White 8 V \sim ⁽¹⁾ or 9 V alkaline battery (not supplied) Class III ⁽²⁾
1	0416 52	230 V \sim 50 / 60 Hz Class II with built-in transformer

Pack	Cat. Nos.	Salsa electronic melodies chime
		Adagio Class III ⁽²⁾ 3 selectable melodies 1 three note melody using additional bell push (not supplied) Adjustable volume control Tone level : 70 - 75 - 80 dB at 1 m Dimensions : 177 x 104 x 45 mm
1	0417 43	White 8 V \sim ⁽¹⁾ or 4 x 1.5 V alkaline batteries (not supplied)

Pack	Cat. Nos.	Surface mounting bell push
		IP 30 - Class III ⁽²⁾ Horizontal or vertical installation Fixing screws not supplied Dimensions : 50 x 25 x 20 mm
5	0416 46	White

Pack	Cat. Nos.	Salsa wireless chime kits
		IP 20 - Class III ⁽²⁾ Radio frequency : 433.92 MHz Operated by push-button transmitter (supplied) Transmitter : 3 x 1.5 V alkaline batteries (not supplied) Receiver : 4 x 1.5 V alkaline batteries (not supplied)

		Alti 1 melody Tone level : 80 dB at 1 m Range : up to 100 metres Dimensions : 120 x 104 x 42 mm
1	0416 15	White Battery operated (batteries not supplied)
		Adagio 2 selectable melodies 1 three note melody using transmitter (not supplied) Adjustable volume control Range : up to 200 metres Tone level : 70 - 75 - 80 dB at 1 m Dimensions : 177 x 104 x 45 mm
1	0416 32	White Battery operated (batteries not supplied)

Pack	Cat. Nos.	Bells with cover
		Surface mounting with levelling facility Tone level : 79 dB at 1 m Dimensions : 95 x 61 x 33 mm
1	0412 19	White 8 V \sim 50/60 Hz ⁽¹⁾ - Class III ⁽²⁾
1	0412 43	230 V \sim 50/60 Hz - Class II with built-in transformer

Pack	Cat. Nos.	Safety isolating transformer
		Conforms to BS 3535-1 and IS EN 60742 and IEC 61558-2-8 Surface mounting, double insulated \square Dimensions : 92 x 56 x 42 mm
1	0420 25	White 230 V \sim primary 8 / 12 V \sim secondary at 1 A
1	0420 27	230 V \sim primary 8 / 12 V \sim secondary at 2 / 3 A

(1) Use with transformer Cat. No. 0420 25
(2) Very low safety voltage

