

# MULTI WAY AUDIO AND VIDEO DOOR ENTRY KITS



## CABLE COMPATIBILITY GUIDE

**bticino**

A brand of **legrand**

POWERED BY SPECIALISTS

## NON POLARISED 2 WIRE TECHNOLOGY

Bticino multi way audio and video kits use non polarised 2 wire technology to make door entry installations simple, reliable and faster to install.

When working on refurbishment projects, 2 wire technology can save even more time by utilising the existing cabling. To check cable compatibility, see p. 3.

For new installations Bticino cable should be used for the best performance.

## FOR INSTALLATIONS REQUIRING NEW CABLING


Bticino Cat. No. 3369 04 and Cat. No. 3369 05 (halogen-free) BUS cable has been designed and manufactured for the installation of video door entry systems.

It consists of a white external sheath with two (brown and brown/white) flexible twisted conductors (0.50 mm<sup>2</sup> section).

Available in a 200 m coil.

It is suitable for use in :

- Free air installation, inside trunking and conduits and on trays
- Inside masonry walls, in appropriate containment
- Underground, in appropriate ducting



## FOR INSTALLATIONS WITH EXISTING CABLING

Where cabling is already installed, please refer to our cable compatibility guide on p. 3




## CABLE COMPATIBILITY GUIDE

The tables below should be used to check the compatibility of existing cable

■ If you require assistance, please contact our technical support helpline on **0370 608 9020** or email **doorentry.uk.technical@legrand.com**


## VIDEO INSTALLATIONS



LINE max. distance	2 core untwisted 0.2 mm	Cat 5 single twisted pair	Telephone single twisted pair 0.28 mm	Bticino 3369 04/3369 05
A	50 m	125 m	125 m	200 m
B	50 m	70 m	70 m	150 m
C	50 m	75 m	75 m	170 m
D	10 m	30 m	30 m	50 m

■ Recommended cable Cat. Nos. **3369 04/3369 05** for best performance  
We cannot guarantee the performance of 3rd party cable suppliers

## AUDIO INSTALLATIONS



LINE max. distance	2 core untwisted 0.2 mm	Cat 5 single twisted pair	Telephone single twisted pair 0.28 mm	Bticino 3369 04/3369 05
A	50 m	125 m	125 m	200 m
B	50 m	70 m	70 m	150 m
C	50 m	75 m	75 m	170 m
D	10 m	30 m	30 m	50 m

■ Recommended cable Cat. Nos. **3369 04/3369 05** for best performance  
We cannot guarantee the performance of 3rd party cable suppliers

## Contact details

### United Kingdom

Great King Street North,  
Birmingham, B19 2LF

### Customer Services:

Tel: +44 (0) 345 605 4333

E-mail: [legrand.sales@legrand.co.uk](mailto:legrand.sales@legrand.co.uk)

### Quotations and Technical Support:

Tel: +44 (0) 370 608 9020

E-mail: [doentry.uk.technical@legrand.com](mailto:doentry.uk.technical@legrand.com)

### Republic of Ireland:

Tel: 01 295 9673

E-mail: [legrand.sales@legrand.co.uk](mailto:legrand.sales@legrand.co.uk)



FOLLOW  
US AT



[www.legrand.co.uk](http://www.legrand.co.uk)  
[www.legrand.ie](http://www.legrand.ie)



[www.youtube.com/legrandtvuk](https://www.youtube.com/legrandtvuk)



[www.twitter.com/legranduk](https://www.twitter.com/legranduk)



[www.linkedin.com/  
company/legranduk](https://www.linkedin.com/company/legranduk)



### Head office (UK and Ireland):

Legrand Electric Limited  
Great King Street North, Birmingham, B19 2LF  
Tel: +44 (0) 370 608 9000  
Website: [www.legrand.co.uk](http://www.legrand.co.uk)